



### HIGH: 180 - 220°C

#### Application:

- Dry Compressors
- Air conveyors
- Industrial Fans
- Packaging machinery
- Ceramic Industry

-30° to +180°C



#### **BHTS 2RS C3 VT 180°**

Seals 2RS for 200° Viton  
Radial Clearance C3  
Lubrication with grease for temperatures up to 200°C

-30° to +200°C



#### **BHTS 2RS C4 VT 200°**

Seals 2RS for 200° Viton  
Radial Clearance C4  
Lubrication with grease for temperatures up to 200°C

-30° to +200°C



#### **BHTS ZZ C4 200°**

Shields ZZ  
Radial Clearance C4  
Lubrication with grease for temperatures up to 200°C

-40° to +220°C



#### **BHTS 2RS C4 VT 220°**

Seals 2RS for 220° Viton  
Radial Clearance C4  
Lubrication with PTFE grease for temp. up to 280°C

-40° to +220°C



#### **BHTS ZZ C4 220°-250°**


Shields ZZ  
Radial Clearance C4  
Lubrication with PTFE grease for temp. up to 280°C

### EXTREME: 250 - 450°C

#### Application:

- Paint Ovens
- Steel industry
- Pyrolysis Oven
- Furnaces for Ceramic Industry
- Trolley for Brick Kilns Industry

-40° to +250°C



#### **BHTS 2RS VT 250°-280°**

Treatment of manganese phosphate  
Seals 2RS Viton  
Radial Clearance 4xC5  
Lubrication with PTFE grease for temperatures up to 280°C

-40° to +280°C



#### **BHTS ZZ 280°**

Treatment of manganese phosphate  
Shields ZZ  
Radial Clearance 4xC5  
Lubrication with PTFE grease for temperatures up to 280°C

-20° to +330°C



#### **BHTS 330°**

Treatment of manganese phosphate  
Open Bearing  
Radial Clearance 4xC5  
Lubrication with Molybdenum disulphide grease


-50° to +350°C



#### **BHTS ZZ GR CG 350°**

Treatment of manganese phosphate  
Shields ZZ  
Radial Clearance 4xC5  
Lubrication from the graphite cage

-40° to +400°C



#### **BHT FB 400°**

Treatment of manganese phosphate  
Open Bearing  
Radial Clearance 4xC5  
Lubrication with Oil for High temp. (on request)  
Full ball fitting


-10° to +350°C



#### **BHTS ZZ 350° BECCO PLUS**

Treatment of manganese phosphate  
Shields ZZ  
Radial Clearance 4xC5  
Lubricated with BECCO grease-compound for temperatures up to 375°C

-10° to +375°C



#### **BHTS ZZ FB 375° BECCO PLUS**

Treatment of manganese phosphate  
Shields ZZ, Full ball fitting  
Radial Clearance 4xC5  
Lubricated with BECCO grease-compound for temperatures up to 375°C

-50° to +450°C



#### **BHT FB 450° BECCO PLUS**

Treatment of manganese phosphate  
Treatment of ceramic coating  
Open Bearing, Full ball fitting  
Radial Clearance 4xC5  
Dry Lubrication

### BECCO PLUS

designation belongs to the bearings with the most efficient performances that use the latest technologies and lubrication systems.

BeCo Plus bearings are state-of-the-art for extreme temperature applications.